



Report of Analysis

Submission:

2005-005500-NYHB

Customer:

Vitol

Terminal:

SPRAGUE RENSSELEAR, NY

Vessel:

TENNESSEE

Product:

#6 FUEL OIL

Date Received:

25-Dec-05

Date Analyzed:

25-Dec-05

Date Reported:

25-Dec-05

Lab Reference: 2005-005500-NYHB-016

Sample Designated As: Shore Tank 15 After Discharge Equal UML Composite NO. 6 FUEL OIL

Method	Test	Results	Units
D4052	API Gravity @ 60 Deg F	10.8	deg API
D93 method B	Corrected Flash Point	>200	deg F
D4294	Sulfur	1.31	Wt %
D445/D2161	Kinematic Viscosity @ 122°F	248.5	cSt
D445/D2161	Saybolt Furol Viscosity @ 122 °F	117.5	SFS
D97	Upper Pour Point	-6	deg C
D97	Upper Pour Point, deg F	21	deg F
D1796	Sediment and Water	0.2	Vol %
D95	Water	0.5	Vol %
D473	Sediment by Extraction	0.04	Wt %
D482 @ 775 deg C	Ash @ 775 deg C	0.053	Wt %
ICP	Sodium	14	ppm
ICP	Vanadium	69	ppm
D5762	Nitrogen	0.31	Wt %
D240	Gross Heat of Combustion	18294	BTU/lb
D240	Gross Heat of Combustion	151493	BTU / gal
D3279	Asphaltene / n-Heptane Insolubles	4.45	Wt %
D4530	Micro Carbon Residue	9.8	Wt %

SPRAGUE PROVIDES THE ATTACHED INSPECTION REPORT/ANALYSIS REPRESENTING THE SPECIFICATIONS OF THE PRODUCT AT THE SPRAGUE TERMINAL IN TANK ON THE DATE OF INSPECTION NOTED ON THE CERTIFICATE. THIS ANALYSIS IS PROVIDED TO THE CUSTOMER FOR THE PURPOSE OF ESTABLISHING THE INDEPENDENTLY VERIFIED PRODUCT SPECIFICATION ON A COMPOSITE BASIS IN SPRAGUE'S TERMINAL SHORE TANK AS NOTED ON THE CERTIFICATE THE INSPECTION REPORT IS NOT TO BE USED FOR ANY OTHER PURPOSE. SPRAGUE DISCLAIMS ANY LIABILITY FOR THE PRODUCT AFTER DELIVERY BY SPRAGUE TO CUSTOMER. SPRAGUE DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR AN INTENDED USE EXCEPT AS MAY BE SPECIFICALLY SET FORTH IN WRITING IN ANY CONTRACT OR TERMS OF SALE BETWEEN SPRAGUE AND A BUYER OF PRODUCT. SPRAGUE ASSUMES NO LIABILITY FOR CLAIMS OR LOSSES THAT MAY ARISE FROM CUSTOMER'S USE OF THIS INSPECTION REPORT/ANALYSIS.

On File	
Intertek Caleb Brett	